




Specification

UTP CAT5e Network Cable 24AWG

CCA



	Product Description:	
1	Cable type/category	UTP CABLE CAT5e
2	Wire substance	Copper (20 % copper) Clad Aluminium conductor
3	Layout	4 Pairs, 24AWG, PVC, Twisted
4	Foil	None
5	Jacket	PVC

	Specification:	
1	Specification	4 Pairs
2	Rated Temperature	60°C or 75°C
3	Pairs	Unshielded twisted pairs
4	Conductor	Copper Clad Aluminium(CCA)
5	Insulator	PVC
6	Unrip rope	Optional
7	Jacket	PVC
8	Impedance	100±15%Ω at 1~100MHz
9	Reference Standard	YD/T1019-2001,ISO/IEC11801,ANSI/TIA/EIA-568B,UL 444
10	Flame Retardancy	Passed CM or CMR



	Feature:	
1	Connection	Fast and reliable connection
2	Usability	Twisted pairs with bright color for easy recognition
3	Application	Ripcord and foot-mark for convenient use
4	Design	Smooth jacket for easy pulling in tight space
5	Colors	Light gray, blue, white or as per customer's requirements
6	Conductor	CCA 0.50(+0,01mm)

	Applications:
1	Computer network cabling project
2	Broadband network communication
3	Digital ISDN and ATM 155Mbps network
4	Ethernet network
5	Audio and data transmission

Packing: 305m/Roll 2Roll/Ctn

